

OceanTools

C4 Subsea Camera

High Definition Internet Protocol camera

The **C4** range of cost-effective subsea Internet Protocol cameras capture HD video in low light level conditions, with a choice of lens options and depth ratings down to 3000m.



C4-10

Overview


The **C4** subsea camera range has been designed to serve a wide range of roles underwater, operating in low light conditions, with a 120dB Wide Dynamic Range. It has rapidly become established as the IP camera of choice for many industries including offshore renewables, salvage, military and scientific research.

The **C4-10** has a fixed zoom with a 4mm lens fitted as standard for 88° field of view. 2.8mm wide or 6mm narrow lens options are available on request.

Colour HD video (including 1080p) is streamed using standard Internet Protocols such as the RTSP protocol, with a remote configuration interface. Lower definition streams including 720p and 360p and a range of video bit rates are also supported.

The compact subsea camera units are manufactured from acetal or anodised aluminium to achieve a 300m or 3000m depth rating respectively with the same dimensions.

A single subsea connector supports data and power, with optional Power over Ethernet (PoE) for easy integration. Multiple IP cameras networked underwater can share a common copper or fibre uplink to the surface.



OceanTools

C4 Subsea Camera

High Definition Internet Protocol camera

Zoom and Fisheye Options

The **C4-20** has a remotely controllable optical zoom for close-up inspection. A versatile 2.8–12mm motorised varifocal zoom lens is fitted as standard. Its housing has a similar design to the **C4-10**, with a choice of 300m or 3000m depth rating and a single subsea connector.

The **C4-30** features an ultra wide angle fisheye lens, paired with an innovative hemispherical window to offer a near 180° field of view. It is also available as either a 300m or 3000m rated unit, with a choice of side or rear connector positions to allow different mounting arrangements.



C4-20 Zoom




C4-30 Fisheye

Related Products

The **C3** range of ultra-compact subsea tooling cameras offer high quality video in low light level conditions, with 750TVL resolution SD composite video or HD-SDI output options. Titanium housings with an 8000m depth rating are available.

The wider OceanTools subsea camera range includes mono and colour diver, ROV navigation and underwater worksite cameras, plus a number of professional HD cameras.

The OceanTools range of high performance subsea LED lamps includes the compact **L3** light and the versatile **L5** that supports serial, analogue or Ethernet control. Both are available with a choice of spot or flood light output and depth ratings down to 8000m.



OceanTools

C4 Subsea Camera

High Definition Internet Protocol camera

Specifications

	C4-10	C4-20	C4-30
Lens type	Fixed	Varifocal Zoom	Fisheye
Focal length	4mm	2.8–12mm	1.05mm
Field of view	88°	115–35°	Near 180°
CMOS sensor size	1/2.5"	1/2.5"	1/2.5"
Maximum resolution	2688 x 1520 (4MP)	3840 x 2160 (8MP)	2560 x 1920 (5MP)
Minimum illumination	0.008 Lux/F1.2	0.01 Lux/F1.2	0.01 Lux/F1.2
Compression standards	H.265+ / H.265 / H.264+ / H.264 / MJPEG		
Network protocols	RTSP / FTP / DHCP / UPnP		
Interface standards	ONVIF (Profile S & G) / PSIA / ISAPI		
Network interface	10M/100M Ethernet		
Input voltage	12–24VDC or PoE 802.3af		
Maximum current	0.7A @ 12VDC	1.5A @ 12VDC	0.5A @ 12VDC
Depth rating	300m or 3000m		
Housing material	Delrin (300m) or Aluminium (3000m)		
Standard connector	Glenair G55 (others on request)		
Connector position	Rear		Side or Rear
Length (excl connector)	105mm	132mm	100mm
Diameter (excl connector)	110mm	125mm	160mm
Weight in air	0.8kg (300m) or 1.7kg (3000m)	1.6kg (300m) or 3.0kg (3000m)	2.0kg (300m) or 5.2kg (3000m)
Weight in water	0.1kg (300m) or 0.6kg (3000m)	< 0kg (300m) or 1.5kg (3000m)	0.6kg (300m) or 4.5kg (3000m)
Operating temperature	-30°C to +60°C		

Product datasheets, GA drawings, case studies and other supporting documents are available to download from data.oceantools.co.uk

All specifications are subject to change without notice. E&OE.

Version 6 (14.10.2020)



OceanTools Ltd
 OceanTools House Claymore Drive Aberdeen AB23 8GD
 t: +44 1224 709 606 e: sales@oceantools.co.uk
www.oceantools.co.uk