



OceanTools

D9 DyeTector®

Diver held subsea dye detection system

The **D9 DyeTector** is a state of the art diver held subsea leak and cement dye detector developed by **OceanTools** based on many years of experience detecting subsea dyes.



Overview

The diver held **D9 DyeTector** may be used to detect leaks from subsea infrastructure such as manifolds, wellheads or pipelines if a suitable dye has been added to the infrastructure fluids, or during casing cementing operations to detect cement returns.

High intensity LED light is focused through lenses and filters to create a concentrated beam that is tuned to a specific wavelength to cause maximum molecular agitation and fluorescence of the dye. A sophisticated optical multiplier employs light amplification technology to detect even the smallest amounts of fluorescence from the agitated dye molecules. Advanced detection electronics convert the measurements to digital data, displayed directly on the rear of the unit.

The powerful **DyeTector** technology is capable of detecting single photons of light. It can detect down to single digit parts per billion of dye dissolved in water and is approximately one hundred times more sensitive than the human eye. This makes it ideal for detecting the very smallest of leaks or traces of dye dosed cement.



OceanTools

D9 DyeTector®

Diver held subsea dye detection system

Operation

The diver held **D9 DyeTector** is a self-contained unit featuring ruggedised single switch operation, a built-in 2.2" detection display and a depth rating in excess of 250m.

The unit is ideally balanced with centre of gravity at the front face of its ergonomic handle. It can be powered using an external portable battery pack via a tidy cable that exits from the end of the handle near the operator's wrist without impeding safe operation.

Detection Dyes

As well as offering the **DyeTector**, OceanTools has a dye that has been specifically developed by our friends at Offshore Environmental Oils to precisely match the characteristics of the **DyeTector**. In short, there is no system more capable of detecting dye subsea, nor is there a more detectable dye.

Versions of the **DyeTector** are designed to excite and detect specific types of dye in addition to OceanTools **C-Dye** and **C-Dye 370**, including:

- Rhodamine dyes such as B275, RX9022, Pelagic 100 Pink
- Fluorescein dyes such as HW443, HW540P, Oceanic Yellow LTF
- Ultraviolet dyes such as RX9026E, Pelagic 100, Champion Cleardye, Castrol HT2

Please contact OceanTools for advice on other dyes that may be detected by the **DyeTector**.

Key Features


- Self contained diver held system
- Rhodamine, Fluorescein or Ultraviolet dye detection
- Focused beam and filtered high intensity LEDs
- Light amplification and photon detection technology
- 250m+ standard depth rating



Related Products

D7 DyeTector systems (pictured above) are ROV mounted leak and dye detection units with up to 6000m depth rating and simple and intuitive software that displays detection data at the surface.

D3 and D5 DyeLighter systems are a modern replacement for old-fashioned "black lights" that agitate fluorescing dye to allow larger leaks to be detected visually by diver or ROV camera.



OceanTools

D9 DyeTector®

Diver held subsea dye detection system

Applications

The **DyeTector** may be used to detect leaks from subsea infrastructure such as manifolds, wellheads or pipelines if a suitable dye has been added to the infrastructure fluids. Pipeline or flow line pressure testing can be monitored by the **DyeTector** if dye impregnated fluids are used.

The **DyeTector** may also be used during casing cementing operations to detect cement returns. A tracer dye is added to either the seawater spacer or to the cement itself. Unlike pH meters which rely upon the cement passing over them, a **DyeTector** can detect cement from a distance of several metres depending on the dye concentration.

Specifications

	D9-R	D9-F	D9-U
Target dye	Rhodamine	Fluorescein	Ultraviolet
Excitation wavelength	520–530nm	450–460nm	360–370nm
Detection wavelength	570–590nm	510–520nm	410–450nm
Detection range	Up to 10m		
Input voltage	18–36VDC		
Maximum current	0.7A @ 24VDC		
Depth rating	250m+		
Housing materials	Anodised Aluminium and Delrin		
Window material	Acrylic		
Display	2.2" TFT LCD (qVGA)		
Body length	180mm		
Body diameter	97mm		
Overall height (incl handle)	280mm		
Weight in air	2.2kg		
Weight in water	1.1kg		

Product datasheets, GA drawings, case studies and other supporting documents are available to download from data.oceantools.co.uk

All specifications are subject to change without notice. E&OE.

Version 2 (06.08.2020)



OceanTools Ltd
OceanTools House Claymore Drive Aberdeen AB23 8GD
t: +44 1224 709 606 e: sales@oceantools.co.uk
www.oceantools.co.uk